



# FHQ-B / RXS-F

# Ceiling Suspended Unit



FHQ60B



RXS60F




BRC1D52

BRC7E63



- > Can be installed in both new and existing buildings
- > Wider air discharge thanks to Coanda effect: up to 100 degrees



- > Home leave operation saves energy during absence
- > Air flow distribution for ceiling heights up to 3.8m without loss of capacity
- > The unit can easily be mounted in corners and narrow spaces, as it only needs 30mm lateral service



## HEATING & COOLING

INDOOR UNIT				FHQ60BVV1B
Capacity	Cooling	Standard	kW	5.7
	Heating	Standard	kW	7.2
EER / COP	Cooling / Heating			2.65 / 2.89
Annual energy consumption			kWh	1075
Energy Label	Cooling / Heating			D / D
Dimensions	Height x Width x Depth		mm	195x1160x680
Weight			kg	27.0
Air Flow Rate	Cooling	High/Low	m <sup>3</sup> /min	17.0 / 13.0
	Heating	High/Low	m <sup>3</sup> /min	16.0 / 13.0
Sound Power	Cooling	High/Low	dBA	55.0 / 49.0
	Heating	High/Low	dBA	55.0 / 49.0
Sound Pressure	Cooling	High/Low	dBA	39.0 / 33.0
	Heating	High/Low	dBA	39.0 / 33.0
Refrigerant			Type	R-410A
Power Supply				1~/220-240V/50Hz

OUTDOOR UNIT				RXS60F2V1B
Dimensions	Height x Width x Depth		mm	735x825x300
Weight			kg	48
Operation Range	Cooling	Min~Max	°CDB	-10~46
	Heating	Min~Max	°CWB	-15~18
Sound Power	Cooling		dBA	63
Sound Pressure (Standard)	Cooling		dBA	49
	Heating		dBA	49
Sound Level (Night quiet)	Sound Pressure		dBA	46
Refrigerant			Type	R-410A
Power Supply				1~/220-240/220-230V/50Hz
Piping connections	Liquid (OD)/Gas/Drain		mm	6.35 / 12.7 / 18
Piping Length (Maximum)			m	30