

# FXLQ-P

20-25-32-40-50-63

## Floor Standing Unit



FXLQ20-25P



BRC1E51A


BRC7C62

### Comfort


- › Stylish modern casing finished in pure white (RAL9010) and iron grey (RAL7011)
- › Unit can be installed as free standing model by use of optional back plate
- › Ideal for installation beneath a window
- › Home leave operation saves energy during absence

### Flexible Installation

- › Requires very little installation space, only 232 mm deep and 600 mm high
- › Wall mounted installation facilitates cleaning beneath the unit where dust tends to accumulate
- › Allows multi tenant applications (option PCB required)
- › Wired remote control can easily be integrated in the unit



Wall mounted



Floor standing



\* Not connectable to RXYQ-PR

Detail of the FXLQ-P  
built-in wired remote  
control



## SPECIFICATIONS

| INDOOR UNITS             |                             |                    |                     | FXLQ20P                                     | FXLQ25P | FXLQ32P       | FXLQ40P | FXLQ50P       | FXLQ63P                            |  |
|--------------------------|-----------------------------|--------------------|---------------------|---|---------|---------------|---------|---------------|------------------------------------|--|
| Cooling capacity         | Nom.                        |                    | kW                  | 2.2   | 2.8     | 3.6           | 4.5     | 5.6           | 7.1                                |  |
| Heating capacity         | Nom.                        |                    | kW                  | 2.5   | 3.2     | 4.0           | 5.0     | 6.3           | 8.0                                |  |
| Power input - 50Hz       | Cooling                     | Nom.               | kW                  | 0.049                                       |         | 0.090         |         | 0.110         |                                    |  |
|                          | Heating                     | Nom.               | kW                  | 0.049                                       |         | 0.090         |         | 0.110         |                                    |  |
| Casing Colour            |                             |                    |                     | Fresh white (RAL9010) / Dark grey (RAL7011) |         |               |         |               |                                    |  |
| Dimensions               | Unit                        | HeightxWidthxDepth | mm                  | 600x1,000x232                               |         | 600x1,140x232 |         | 600x1,420x232 |                                    |  |
| Weight                   | Unit                        |                    | kg                  | 27  |         | 32            |         | 38            |                                    |  |
| Fan-Air flow rate - 50Hz | Cooling                     | High/Low           | m <sup>3</sup> /min | 7/6   |         | 8/6           | 11/8.5  | 14/11         | 16/12                              |  |
| Sound power level        | Cooling                     | Nom.               | dBA                 | -   |         |               |         |               |                                    |  |
| Sound pressure level     | Cooling                     | High/Low           | dBA                 | 35/32                                       |         |               | 38/33   | 39/34         | 40/35                              |  |
| Refrigerant              | Type                        |                    |                     | R-410A                                      |         |               |         |               |                                    |  |
| Piping connections       | Liquid/OD/Gas/OD/Drain      |                    | mm                  | 6.35/12.7/O.D. 21 (Vinyl chloride)          |         |               |         |               | 9.52/15.9/O.D. 21 (Vinyl chloride) |  |
| Power supply             | Phase / Frequency / Voltage |                    | Hz / V              | 1~ / 50/60 / 220-240/220                    |         |               |         |               |                                    |  |